

Murphy[®] Oil Soap Original Formula

Finished wood paneling
Laminated surfaces
Cabinets
Paneling
Painted wood
Formica
Tables and chairs
Bookcases
No-wax floors
Plastic
Ceramic tile
Marble
Painted surfaces
Enameled surfaces
Laundry stains
Acrylic fiberglass
Linoleum/Vinyl



How to Use Murphy Oil Soap Original Formula

For most jobs, including wood floors, use 1/4 cup of Murphy Oil Soap Original Formula to one gallon of warm water (two ounces of Murphy's to 128 ounces of water). Start with a clean, well wrung-out mop. Be sure to mop up any excess water. For tougher jobs, use 1/2 cup of Murphy's to one gallon of warm water.

Use these wood care tips from the Murphy's wood experts, and keep your wood looking its best.

Exposure to sunlight can speed the aging of wood. To prevent UV exposure from fading wood's natural color, consider installing curtains or blinds to block direct sunlight.

Use coasters to protect wood-topped tables from water rings. For a more permanent water-ring solution, ask your hardware store to cut a glass or Plexiglas pane to fit your wooden table top.

Remember, wood is dynamic and will expand and contract with extreme fluctuations of humidity and temperature. Avoid extremes of hot, cold and wet to prevent cracking of solid-wood furniture